


Roto TSL Twin Cam Security Locking System



Roto TSL can be used on windows with a shallow or full depth Eurogroove from as little as 305mm all the way up to 1600mm. Up to 4 pairs of adjustable steel mushroom headed cams lock into both sides of double entry night vent striker plates to provide a smooth closing action and excellent security. TSL is designed to meet the demands of security standard PAS24:2012.

Roto have utilised the faceplate from their NT tilt and turn range for the TSL. The faceplate is stepped, or contoured, which not only looks attractive when fitted into a window's Eurogroove, but also adds stability and strength, particularly on longer sizes. The faceplate is marked to correspond with markings on the striker plate to ensure the striker plates are fitted in the optimum position.

The new TSL features Roto Sil Nano surface finish technology, which is extremely scratch resistant and offers outstanding corrosion resistance as standard (480 hours neutral salt spray test according to EN1670:2007 grade 5).

A version with low handle height position (205mm) is also available in the 9.5mm mushroom variant. This meets the requirements of the Lifetime Homes standard.

Benefits at a glance:

- Secure window locking system tested to security standard PAS24:2012
- Fits Eurogrooves up to 1600mm
- Quick to fit - no cropping or fitting of extensions/end pieces is required and all fasteners are applied from same direction
- Roto Sil Nano surface treatment meets requirements of EN1670:2007 grade 5 (480 hours)
- NT faceplate for greater stability and pleasing aesthetics
- Low handle height version available (9.5mm MB)
- 10 year Roto functional warranty

SPECIFICATION DATABASE

HWRL - 7/24 - V1.0



Roto TSL Twin Cam Security Locking System

VBH order codes


Standard

Length	MB*	20BS/ 8MB	20BS/ 9.5MB	22BS/ 8MB	22BS/ 9.5MB	Box Qty
300mm	2	2RWE4501	2RWE4511A	2RWE4521	2RWE4531	10
400mm	2	2RWE4502	2RWE4512A	2RWE4522	2RWE4532	10
600mm	2	2RWE4503	2RWE4513A	2RWE4523	2RWE4533	10
800mm	4	2RWE4504	2RWE4514A	2RWE4524	2RWE4534	10
900mm	4	2RWE4505	2RWE4515A	2RWE4525	2RWE4535	10
1000mm	4	2RWE4506	2RWE4516A	2RWE4526	2RWE4536	10
1100mm	4	2RWE4507	2RWE4517A	2RWE4527	2RWE4537	10
1200mm	4	2RWE4508	2RWE4518A	2RWE4528	2RWE4538	10


Low Handle Height Version

Length	MB*	20BS/ 9.5MB	22BS/ 9.5MB	Box Qty
850mm	4	2RWE4565	2RWE4573	10
950mm	4	2RWE4566	2RWE4574	10
1050mm	4	-	2RWE4575	10
1150mm	4	2RWE4568	2RWE4576	10

*denotes quantity of striker plates required



Mushrooms locate into both sides of striker plate



- Nano particles and optical sealing
- Chromium VI-free passivation
- Zinc coating
- Basic material: steel

Roto Sil Nano surface protection